

HandyStep® S

The BRAND® HandyStep® S repeating pipette provides unprecedented versatility in a purely mechanical repeating pipette. In conjunction with BRAND® PD-Tip™ // Precision Dispenser Tips, the HandyStep® S offers nearly sixty different volume settings with accuracy, precision, and dependability.

- **Comfortable**—The slim design of the HandyStep® S is lightweight, well-balanced, and provides a convenient control layout for smooth dispensing and one-handed volume selection.
- **Reliable**—The robust construction, using innovative polymers, delivers a dependable instrument.
- **Ready-to-go**—The mechanical design, with no batteries to charge or replace, means the HandyStep® S is ready when you are. A convenient integrated table provides a quick reference for dispensed volumes.
- **Flexible**—Ten sizes of PD-Tip™ // Precision Dispenser Tips allow the HandyStep® S to dispense 59 different volumes. The open design allows use of third party tips—no more being locked into a sole source.
- **Contact-free**—The tip ejection system allows tip removal without handling.

More than just precise—
slim, light, and dependable



Technical Data

Operating limits and exclusions

Liquids unsuitable for use with the HandyStep® S include, but are not limited to, those with:

- Vapor pressure exceeding 500 mbar
- Viscosity: 20 mPa s with 50 mL PD-Tips™ //; 260 mPa s with 5 mL PD-Tips™ //; 977 mPa s with 1 mL PD-Tips™ //
- Reagents that attack PP (PD-Tip™ // cylinder), HDPE (PD Tip™ // piston), LCP (PD-Tip™ // piston 0.1 mL) or PC/PBT and polycarbonate
- Temperature of instrument and reagent must be between 15 °C and 40 °C
- Instrument and tips must not be autoclaved

Items supplied

The HandyStep® S is supplied with the following items:

- Performance certificate
- Shelf/rack mount
- One each: 0.1 mL, 1 mL and 10 mL PD-Tip™ // Precision Dispenser Tips
- Operating manual
- Two-year warranty

HandyStep® S Repeating Pipette

Setting at a glance

Easy to read volume setting indicator

Chart topper

Tip/volume chart assists with tip selection and volume setting

Perfectly aligned

Dispensing lever optimally positioned for easy thumb movement

Big wheel

Volumes easily adjusted with a simple thumb movement

Simple

Combined piston locking/filling lever makes aspiration easy

Comfortable

Finger rest provides balance, convenient control access, and relaxed pipetting

Hands-free disposal

Ergonomic tip ejector, for safe and contact-free ejection of contaminated dispenser tips



Shelf/rack mount

Shelf/rack mount keeps your HandyStep® S close at hand and retrofits to Transferpette® S carousel stand



Flexible

Compatible with PD-Tip™ II Precision Dispenser Tips, as well as many third-party tips

HandyStep® S with BRAND® PD-Tip™ II Precision Dispenser Tips

Accuracy Table

Nominal Volume PD-Tip™ II, mL	Volume Range, μL	Stroke setting ▲ % of nominal volume (A* ≤ ± %)			Stroke setting ▲ % of nominal volume (CV* ≤ %)		
		1 ▲ 2%	3 ▲ 6%	5 ▲ 10%	1 ▲ 2%	3 ▲ 6%	5 ▲ 10%
0.1	2-10	4.0	2.4	1.6	6.0	3.0	2.0
0.5	10-50	2.5	1.5	1.0	2.5	1.5	1.0
1	20-100	2.5	1.5	1.0	2.0	1.2	0.8
1.25	25-125	2.5	1.4	0.9	2.0	1.1	0.7
2.5	50-250	1.8	1.1	0.7	1.5	0.9	0.6
5	100-500	1.8	1.1	0.7	1.5	0.9	0.7
10	200-1000	1.8	1.1	0.7	2.0	1.2	0.8
12.5	250-1250	1.8	1.1	0.8	3.2	2.0	1.4
25	500-2500	1.5	0.9	0.6	3.04	1.5	1.0
50	1000-5000	1.5	0.8	0.5	5.0	1.8	1.2

A*=Accuracy, CV*=Coefficient of Variation

*Error limits refer to the partial volume set relative to the PD-Tip™ II, obtained when instrument, PD-Tip™ II and distilled water are equilibrated at ambient temperature (20 °C) and with smooth operation. The testing is according to DIN EN ISO 8655-5.

Note: the nominal volume is the maximum adjustable partial volume for each PD-Tip™ II size.

Volume table

Setting	1	1.5	2	2.5	3	3.5	4	4.5	5
PD-Tip™ II, mL	Volume, μL								
0.1	2	3	4	5	6	7	8	9	10
0.5	10	15	20	25	30	35	40	45	50
1	20	30	40	50	60	70	80	90	100
1.25	25	37.5	50	62.5	75	87.5	100	112.5	125
2.5	50	75	100	125	150	175	200	225	250
5	100	150	200	250	300	350	400	450	500
10	200	300	400	500	600	700	800	900	1000
12.5	250	375	500	625	750	875	1000	1125	1250
25	500	750	1000	1250	1500	1750	2000	2250	2500
50	1000	1500	2000	2500	3000	3500	4000	4500	5000
Steps	49	32	24	19	15	13	11	10	9

Ordering information

Description	Cat. No.	List Price
HandyStep® S repeating pipette	705110	\$402.80
HandyStep® S shelf/rack mount	705130	33.20

HandyStep® touch

NEW!

- Touchscreen operation with intuitive menu navigation and integrated help function
- Two models available: HandyStep® touch or HandyStep® touch S with expanded functionality

- Menu languages: English, German, Spanish, French and Chinese
- Variable volume adjustment from 1.0 μ L to 50 mL
- Inductive charging with optional charging stand

A closer look

Versatile

HandyStep® touch with the standard modes Multi-Dispensing, Auto-Dispensing, Pipetting and Favorites;

HandyStep® touch S with the additional functions Sequential Dispensing, Multi-Aspiration and Titration

Long-lasting

Many hours of continuous operation with a single battery charge

Robust

High-quality materials provide long service life, and smooth surfaces make cleaning/disinfection easy



USB-C connection

For quick charging by cable

STEP button
Ergonomically arranged STEP button for effortless volume filling and delivery



Easy
Automatic size detection of BRAND® PD-Tip™ II

Efficient
In addition to BRAND® PD-Tip™ II,
compatible third party tips can
also be used.

Simple
Automatic tip ejection by the press
of a button prevents
contamination




Convenient

Inductive charging with the optional
charging stand

HandyStep® touch Repeating Pipette

Be flexible and have the right solution at hand for every application. Even complex procedures are easy to carry out – no problem with the expanded functionality of the HandyStep® touch *S*.

Mode	Function	HandyStep® touch	HandyStep® touch <i>S</i>
Multi Dispensing (MULTI-DISP)	Successive dispensing of a set volume	✓	✓
Auto Dispensing (AUTO-DISP)	Automatic dispensing by the instrument	✓	✓
Pipetting (PIP)	Pipetting a defined volume	✓	✓
Sequential Dispensing (SEQ-DISP)	Successive dispensing of different volumes	–	✓
Multi Aspirating (MULTI-ASP)	Aspirating different volumes	–	✓
Titrating	Manual or successive delivery of liquids for titration	–	✓
Favorites	Saving favorites for quick access	✓	✓
Settings	Individual customization of the device (e.g. brightness or device name)	✓	✓



Functions of the



Expanded functionality

The clearly structured menus make fast work with intuitive operation possible, while the most important functions and parameters are always in view.



Easy to understand
Main menu with all modes for quick selection



Clearly structured
Working mode with all important information



Organized
All options visible at a glance



Helpful
Internal help right where it is needed

HandyStep® touch Repeating Pipette

Technical Data

Operating limits and exclusions

Liquids unsuitable for use with the HandyStep® touch and PD-Tip™ // Precision Dispenser Tips include, but are not limited to, those with:

- Vapor pressure exceeding 500 mbar
- Viscosity: 20 mPa s with 50 mL PD-Tips™ //; 260 mPa s with 5 mL PD-Tips™ //; 977 mPa s with 1 mL PD-Tips™ //
- Chemicals incompatible with tips used, see page 30 for PD-Tip™ // materials of construction ; and polycarbonate (device housing)
- Temperature of instrument and reagents must be between 15° and 40 °C
- The HandyStep® touch cannot be autoclaved

Items supplied

Each HandyStep® touch includes:

- Li-Ion battery
- Universal power adapter
- Shelf/rack mount
- Five assorted volume PD-Tip™ // Precision Dispenser Tips
- Performance certificate
- Operating manual
- One-year warranty

Use the tips you want

The only electronic repetitive pipette compatible with all standard repeating pipette tips. The HandyStep® touch accepts:

- BRAND® PD-Tip™ // Precision Dispenser Tips
- BRAND® PD-Tip™ Precision Dispenser Tips
- Rainin® Encode™ Precision Dispenser Tips
- Eppendorf® Combitips advanced®
- Fisherbrand® Dispenser Tips
- VWR® Combi-Syringes
- Gilson® Repet-Tips

Accuracy and precision for the HandyStep® touch

PD-Tip™ //	Volume Range	Increment	A* < ±						CV* ≤		
			100%	50%	10%	1%	100%	50%	10%	1%	
0.1 mL	1 µL-100 µL	0.1 µL	1	1	1.6	8	0.5	1	2	12	
0.5 mL	5 µL-500 µL	0.5 µL	0.9	0.9	1	5	0.3	0.6	1	5	
1.0 mL	10 µL-1000 µL	1 µL	0.6	0.9	1	5	0.3	0.5	0.8	4	
1.25 mL	12.5 µL-1250 µL	1.25 µL	0.6	0.6	0.9	5	0.2	0.5	0.7	4	
2.5 mL	25 µL-2500 µL	2.5 µL	0.5	0.6	0.7	3.5	0.15	0.3	0.6	3	
5.0 mL	50 µL-5000 µL	5 µL	0.5	0.5	0.7	3.5	0.15	0.4	0.7	3	
10.0 mL	100 µL-10 mL	10 µL	0.4	0.5	0.7	3.5	0.15	0.5	0.8	4	
12.5 mL	125 µL-12.5 mL	12.5 µL	0.5	0.5	0.8	3.5	0.15	0.6	1.4	6.5	
25.0 mL	250 µL-25 mL	25 µL	0.5	0.5	0.6	3	0.15	0.3	1.0	6	
50.0 mL	500 µL-50 mL	50 µL	0.5	0.5	0.5	3	0.15	0.4	1.2	9	

A* = Accuracy, CV* = Coefficient of variation

*Error limits refer to the nominal volumes and partial volumes relative to the PD-Tip™ // obtained with instrument and distilled water at equilibrium with ambient temperature at 20 °C. . The tolerances specified in ISO 8655 are not exceeded. The nominal (100%) volume is the maximum volume which is printed on the PD-Tip™ //.

2021		
Description	Cat. No.	Cat. No.
HandyStep® touch repeating pipette		
HandyStep® touch	705200	\$1,055.00
HandyStep® touch S	705210	1,299.00
Inductive charging stand bundles		
HandyStep® touch & Charging stand	705201	1,148.00
HandyStep® touch S & Charging stand	705211	1,525.00
Accessories		
Charging stand	705220	351.80
Support stand	705230	146.80
Shelf/rack mount	705235	35.60
Universal AC adapter	705250	86.60
Spare battery	705225	81.60



Support stand with HandyStep® touch

Inductive charging with the optional charging stand

NEW!

PD-Tip™ // Precision Dispenser Tips

The perfect team

Automatic size detection with PD-Tip™ // from BRAND®

Patented coding on the pistons of the PD-Tip™ // from BRAND® allows automatic tip size recognition with the HandyStep® touch, saving time and preventing errors. After inserting a PD-Tip™ //, the size is automatically recognized and displayed, making it easy to select the volume to be dispensed. The next time a new PD-Tip™ // of the same size is inserted, all instrument settings are maintained. Easy!



Multi dispensing with the HandyStep® touch and PD-Tip™ //



Sequential dispensing with the

BRAND® encoded PD-Tip™ // Precision Dispenser Tips are manufactured from high-quality virgin plastics for use with all standard repeating pipettes in a wide variety of applications.

- **Compatible**—with most pipettes.

PD-Tip™ // Precision Dispenser Tips are an excellent choice for the BRAND® HandyStep® S, HandyStep® electronic, and HandyStep® touch repeating pipettes; the black-handled Eppendorf® Repeater® 4780*; the Fisherbrand® repeating pipette; the Rainin® AutoRep™ E and AutoRep™ S; the Gilson® Repetman®; and other repeating pipettes using standard tips. PD-Tip™ // Precision Dispenser Tips are encoded for automatic recognition by the BRAND® HandyStep® touch and HandyStep® electronic repeating pipettes, the Rainin® AutoRep™ E, and the Gilson® Repetman®.

- **Reliable**—A precision seal between the piston and cylinder ensures smooth operation, increased accuracy, and increased precision. Extended piston design minimizes dead volume and maximizes fluid utilization.

- **Quality**—Manufactured from high quality materials PD-Tip™ // Precision Dispenser Tips are made entirely from high-quality virgin polyethylene and polypropylene. (Piston of 0.1 mL tip is liquid crystal polymer-LCP).

PD-Tip™ // Precision Dispenser Tips

NEW!

The perfect tips for your repeating pipette

Preserve Sample Integrity with BIO-CERT® quality sterile tips

BIO-CERT® PD-Tip™ // Precision Dispenser Tips are sterile, individually wrapped and certified free of DNA, RNase, endotoxins, and ATP to meet the most stringent sample integrity requirements. For more information on the sterility and purity levels, see page 130.

Calibration support

BRAND® PD-Tip™ // Precision Dispenser Tips are supplied with a batch Certificate of Performance which documents tip accuracy and precision testing.



Capacity, mL	Pack of	PD-Tip //	2021 List Price
PD-Tip™ // Precision Dispenser Tips, non-sterile			
0.1 mL	100	705700	\$125.20
0.5 mL	100	705702	125.20
1 mL	100	705704	125.20
1.25 mL	100	705706	125.20
2.5 mL	100	705708	125.20
5 mL	100	705710	125.20
10 mL	100	705712	125.20
12.5 mL	100	705714	125.20
25 mL, (one adapter included)	50	705716	84.80
50 mL, (one adapter included)	25	705718	42.40
PD-Tip™ // Precision Dispenser Tips, non-sterile, assorted pk. 0.5, 1, 1.25, 2.5, 5, 10 and 12.5 mL sizes	20/size	705720	169.60
Adapter for 25 mL and 50 mL			
PD-Tip™ // Precision Dispenser Tips, non-sterile, PP, autoclavable	10	702398	99.60

Capacity, mL	Pack of	PD-Tip //	2021 List Price
PD-Tip™ Precision Dispenser Tips //, BIO-CERT® sterile			
Individually wrapped			
0.1 mL	100	705730	\$171.60
0.5 mL	100	705732	171.60
1 mL	100	705734	171.60
1.25 mL	100	705736	171.60
2.5 mL	100	705738	171.60
5 mL	100	705740	171.60
10 mL	100	705742	171.60
12.5 mL	100	705744	171.60
25 mL, (one adapter included)	25	705746	52.60
50 mL, (one adapter included)	25	705748	52.60
Adapter for 25 mL and 50 mL PD-Tip™ // BIO-CERT® sterile, PP, autoclavable	5	702399	78.40

*The Eppendorf Repeater Plus, Repeater® M4, Repeater Pro, Stream, XStream, E3 and E3x are designed to preclude their operation with any tips other than Eppendorf Combitips advanced®.